

Datatek Systems Inc

Model AT505A

Molybdenum based converter

Specifications:

Mounting: Panel or DIN rail

Operating Temperature Range: 0-500 C

Flow rate: < 1.5 LPM

Voltage: 115 VAC 60 HZ 2amp

Molybdenum load: 50 gram

Converter dimensions: 9in X 3.5in X 3.5in

Converter Wetted Material: 316 SS

Ports: 1/4" FNPT

Control Sensor: K type thermocouple

Warranty: 1 year, does not include Molybdenum



When Nox readings are a requirement and your onboard converter has seen better days, maybe it's time to think outside the box (analyzer box, that is). Our external Nox Converter gives you the same conversion capabilities as any in the analyzer type without heating up delicate electronics. Conversion unit can be rail mounted or panel and easily plumbed to existing equipment without changing the flow path.

Complete unit with controller P/N AT505A \$850.00

Options:

Panel mounted Controller, for ease of mounting \$125.00

10 Amp relay (for extended life of controller) \$ 65.00

Molybdenum Renewal (includes 50 gram MO, vacuum tested) \$275.00

Datatek 4464 McGrath Street, Suite 115, Ventura, CA 93003

805.825.2995

Sales@datateksystems.com

Bobd@datateksystems.com